

















Joining the Quilted Blocks

			
<p>1. Pin 1" Joining strip to Block. Right side facing.</p>	<p>2. Turn Block over and pin 1 3/8" Joining strip to Back of Block</p>	<p>3. Sew 1/4" seam thru all 3 layers.</p>	<p>4. Press 1" Joining strip outward. Keep Back Joining strip in place.</p>
			
<p>5. Trim Top and Bottom Joining strip.</p>	<p>6. Place second block to the right of the first block.</p>	<p>7. Place second block on top of first block, right sides facing.</p>	<p>8. Turn blocks over. Pin 1" Joining strip to second block. Sew 1/4" seam.</p>
			
<p>9. Press the Joining strip.</p>	<p>10. Turn block over. Blocks should be flush.</p>	<p>11. Press 1 3/8" Joining strip over the seams.</p>	<p>12. Fold 1 3/8" Joining strip so that the edge is just under the Seam. Press Fold</p>
			
<p>13. Place Steam a Seam or something similar on the folded edge.</p>	<p>14. Remove the paper from Steam a Seam and press folded Joining strip over the seam.</p>	<p>15. Stitch in the Ditch to secure the Joining strip.</p>	<p>16. Back Joining strip will be secure. Or hand sew Back Joining strip.</p>